

User manual

CALA® SR

Welcome.

We are delighted that you have decided to purchase a **T+A** product. With your new **CALASR** you have acquired a top-quality piece of equipment which has been designed and developed with the wishes of discerning listeners as absolute top priority.

This system represents our very best efforts at designing practical electronic equipment incorporating solid quality, user-friendly operation and a specification and performance which leaves nothing to be desired.

All these factors contribute to a piece of equipment which will satisfy your highest demands and your most searching requirements for a period of many years. All the components we use meet the German and European safety norms and standards which are currently valid. All the materials we use are subject to painstaking quality monitoring.

At all stages of production we avoid the use of substances which are environmentally unsound or potentially hazardous to health, such as chlorine-based cleaning agents and CFCs.

We also aim to avoid the use of plastics in general, and PVC in particular, in the design of our products. Instead we rely upon metals and other non-hazardous materials; metal components are ideal for recycling, and also provide effective electrical screening.

Our robust all-metal cases exclude any possibility of external sources of interference affecting the quality of reproduction. From the opposite point of view our products' electro-magnetic radiation (electro-smog) is reduced to an absolute minimum by the outstandingly effective screening provided by the metal case.

Our range of accessories includes high-quality cables and connectors

We would like to take this opportunity to thank you for the faith you have shown in our company by purchasing this product, and wish you many hours of enjoyment and sheer listening pleasure with your CALA SR.

T+A elektroakustik GmbH & Co KG









About these instructions

All the controls and functions of the CALASR which are frequently used are described in the first section of these operating instructions.

The second part 'Basic settings, Installation, Using the system for the first time' covers connections and settings which are very seldom required; they are generally required only when the machine is set up and used for the first time. Here you will also find a detailed description of the network settings required for connecting the CALASR to your home network.

Symbols used in these instructions



Caution!

Text passages marked with this symbol contain important information which must be observed if the machine is to operate safely and without problems.



This symbol marks text passages which provide supplementary notes and background information; they are intended to help the user understand how to get the best out of the machine.

Notes on software updates

Many features of the CALASR are software based. Updates and new features will be made available from time to time. The update process takes only a few minutes. See the chapter entitled "Software update" for how to update your device via the internet connection. We recommend you to check for updates before using your CALASR for the first time. To keep your device up to date you should check for updates from time to time.



The operation instructions, the connection guidance and the safety notes are for your own good - please read them carefully and observe them at all times. The operating instructions are an integral part of this device. If you ever transfer the product to a new owner please be sure to pass them on to the purchaser to guard against incorrect operation and possible hazards.



All the components we use meet the German and European safety norms and standards which are currently valid. This product complies with the EU directives 2014/35/EC, 2014/30/EC, 2009/125/EC, 2011/65/EC + 2015/863, 1999/5/EC and 2012/19/EC.

Contents

CALA SR Audio System	
Display	8
Screen symbols and their meaning	
Remote Control	10
Basic Functions of the Cala	13
Source switching	13
Volume control	
Switching outputs	
Tone settings (Tone menu)	
Balance	
Loudness	
Tone Control	
Treble	
Mid	
Bass	
Subwoofer	
Contour Presence	
Contour Fundamental tone	
Mode of operation	15
Stereo / Virtual Surround	15
Basic settings of the CALA SR	16
Calling up and operating the menu	
• • • •	
Speaker	
Speaker LF ShapeSPK stand	
Room	
Subwoofer	
OUT / Phones	
Source settings	
Available	
Source name	
Passthrough	
Phono mode	
Input level	
Display brightness	
Display mode	
Ambient brightness	
Ambient colour	
Ambient colour cycling	20
Language	20
Device name	
Network	20
Music services	20
Bandwidth limit	21
Energy saver	21

	Device Info	.21
Alarm	Timer	22
	Alarm function	
	Switching the Timer off	
	Quick selection menu	
Alar	m Timer menu	
	Calling up and operating the menu	
	Menu item	
	Alarm Time	_
	Alarm Source	
	Alarm Vol.	
	Time Mode	
	Set Time	
	Time display	
	Show clock	
Cl	Brightness Clock	
Siun		
	Activate slumber function	
	Turn off slumber function	
	ing the sources in detail	
Favo	purites lists	
	General information	
	Calling up the Favourites list	
	Adding a favourite Erasing a favourite from the Favourites list	.25 26
	Selecting a favourite from the list	
	Directly selecting a favourite	
	Sorting Favourites lists	
Ope	rating the radio	28
	M - Radio	
	Selecting FM radio	
	General	
	Manual station search	
	Automatic station search	
	Selecting a station from the Station list	
	RDS functions	
	Mono / Stereo	
D	AB - Radio	
	Selecting DAB radio	.30
	Display	.30
	Automatic station search	
	Selecting a station from the Station list	
In	RDS functions ternet-Radio	

Selecting Internet Radio as source	32
Selecting podcasts	
Playback	_
Favourites lists	
Search function	
Operating music services	
General information	
Selecting the music service	
PlaybackSearch function	
Playlists and favourites	
Operating the SCL source (Streaming Client)	
General information on the streaming client	
Playback	
Playback of directories	
Search function	
Playing USB memory media (USB Media source)	38
General information	
Selecting USB Media as source	
Playback	38
Playback of directories	
Search function	
Operating the Bluetooth Receiver	
Selecting Bluetooth	
Setting up audio transfer	
Playback functions Volume adjustment	
Notes	
The Cala as D/A Converter	
General Information on D/A Converter Operation	
D/A Converter Operation	
Selecting a D/A Converter Source	
Front panel display	
Installation, Using the system for the first time, Safety notes	43
Back panel connections	44
Installation and wiring	47
Loudspeaker and signal cables	
,	
Safety notes	
Network Configuration	52
The Configuration for a Wired Ethernet LAN or Power-Line LAN	
connection	54
Setting the Parameters for a Wired Network	
The Configuration for a WLAN connection	56

Setting the parameters for a wireless network	56
Selecting and connecting a WLAN by hand	56
Searching for and Selecting the Network	56
Entering the Password (for encoded networks)	
Storing Network Settings and Restarting	
Connecting to WLAN via the WPS-function	57
WPS-function	57
Connecting WLAN automatically via the WPS function	
Selecting the WLAN manually and conneting via WPS	57
Trouble shooting	50
Trouble Shooting	
Software update	61
Software update generally	61
Updating via the Internet	
Notes on Energy Saving	62
General information	
Automatic power-down (Energy saver)	
• • • • • • • • • • • • • • • • • • • •	
Appendix A	
Wiring diagram	63
Appendix B	65
Specification	

CALA SR Audio System




All the functions of the CALASR are operated using the FM1000 remote control handset. Direct-access buttons are provided for the essential functions such as source select and track select, whereas less frequently required functions are controlled by means of menus which are called up using the (sys) button.

Display

All information relating to machine status, the current music track and list navigation is displayed on the graphic screen of the CALASR. The display is context-sensitive, and in part varies according to the capabilities and facilities of the service to which you are currently listening.

The most important information is highlighted on the screen according to context. Supplementary information is provided by symbols above and below the main data (please see next page)..



The basic areas of the screen:

- Display field (a) shows the currently active source.
- Display field (b) shows information relating to the piece of music being played. The essential information is displayed enlarged in the main line.
- Display field (c) shows information relating to the device and playback.
- The bottom line (d) displays supplementary context-sensitive information (e.g. sampling frequency, elapsed time)
- The CALASR provides different screen displays for the Streaming Client and the radio.
 - Large-format display:
 Enlarged display of the most important information, clearly legible even from a distance
 - Detail display: Small-text display showing a large number of additional information points, e.g. bit-rate etc.

Screen symbols and their meaning

•	Making connection (Wait / Busy) The rotating symbol indicates that the CALASR is currently processing a command, or is attempting to connect to a service. These processes may take some time to complete depending on the speed of your network and the load upon it. During such periods the CALASR may be muted, and may not respond to the controls. Please wait until the symbol disappears, then try again.
7	Indicates a music track which can be played , or a playlist.
	Indicates a folder which conceals further folders or lists.
±D/	Indicates that a source is being reproduced via a cable connection .
<u></u>	Indicates that a source is being reproduced via a radio connection .
•	Indicates that the CALA SR is reproducing a station or playing back a music track.
II	Pause indicator
₹ (Indicates that the speakers are switched off.
☐ 1:20 128 k	Buffer display (fullness indicator, memory display) and data rate indicator (if available): The higher the data rate, the better the quality of reproduction.
<u>©</u> 1:20	Display of the elapsed playback time. This information is not available for all services.
←	Indicates that the button can be used to switch to a higher menu or select level.
0/0	Position indicator in select lists. The first number shows the current position in the list, the second number the total number of list entries (length of list).
ABC or abc or 123	Display of the symbol input modes
Д 8:30	Indicates that an alarm time is set and active

Remote Control

Introduction

The infrared receiver for the remote control handset is located left of the screen area. There must be line of sight contact between the **FM1000** and the screen.

The following tables show the remote control buttons and their function when operating the machine.



(red)	Switches the machine on and off
(SCL/USB)	Selects the SCL function (e.g. access to music servers or similar), or selects the USB Media function (connected USB memory media) of the streaming client. Press this button repeatedly until the desired source appears on the screen.
AIN	A brief press on this button selects the analogue input you wish to use. Press the button repeatedly until the desired input is displayed on the screen.
DIN	A brief press on this button selects the digital input you wish to use. Press the button repeatedly until the desired input is displayed on the screen.
RADIO	Selects FM, DAB, or Internet radio as source. Press this button repeatedly until the desired source appears on the screen.
BT	Selects the Bluetooth function
abc 9 XYZ 0	Direct alpha-numeric input, e.g. track number, quick station select, radio station. The buttons
(green)	Switching between the following modes of operation: STEREO and VIRTUAL SURROUND.
(yellow)	Switches sound on and off (MUTING) A brief press switches the speaker outputs on and off. A long press switches the analogue output (preout / headphones) on and off.

(yellow)	Reduces / increases volume (volume control rocker)
SYS	Menu A brief press: Opens the "System configuration" menu. (for details see Chapter "Basic settings of the CALA SR") A long press: Opens the Alarm timer menu.
SRC	Opens the setup menu for the source device just selected. (Not all sources have their own Setup menu.)
	Tone settings Brief press opens the tone control settings menu:
	Navigation
	Returns to the previous point / change button
	Confirms the input / change button
	Selects the next point within a list / select button
	Selects the previous point within a list / select button
OK	Confirmation button during input procedures
	Playback functions
I	Starts playback (Play function) During playback: halts (Pause) or resumes playback
	A brief press stops playback. During menu navigation : a brief press takes you back (higher) by one menu level or aborts the current input process; the change is then abandoned.
₩.	Selects the previous track during playback.
₩)	Selects the next track during playback.
•	Rewind to search for a particular passage. FM Radio: Manual station search
>>	Fast-forward to search for a particular passage. FM Radio: Manual station search

<u> </u>	Adds a favourite to the Favourites list.
8	Long press: Removes a favourite from the Favourites list.
<u> </u>	Button for switching between Stereo and Mono reception (only FM Radio) The Stereo setting is constantly displayed in the screen window by a symbol. The Mono setting is constantly displayed in the screen window by a symbol.
A	Switches between numeric and alpha-numeric input, and between capitals and lower case when pressed (repeatedly) Calls up the search function for SCL, USB-Media, Internet radio, Podcasts and Music services. Activates the sort function within a Favourites list.
	Displays the Favourites list created on the CALASR
•	Switches the display from the track list / station list navigation to the ,Now Playing' view. Switches the Radio text function ON/OFF. A long press toggles between different screen displays.

CALASR can be controlled by the **T+A** App 'TA Control' too. For further information please visit our homepage www.ta-hifi.com

Basic Functions of the Cala

The basic functions of the CALASR, described in this chapter are always available, regardless of the selected source.

Source switching

The source buttons are used to select the desired internal source (FM Radio, DAB Radio, USB Media, Streaming Client oder Internet) or an external source (Analog In 1, Analog In 2, Bluetooth, Digital 1 -3) for playback.

Once the CALASR has switched to the internal sources they can be operated using the remote control.

Please refer to the following chapters for details of operating the individual source devices.



Sources which are not in use can be disabled in the System Configuration menu. This can make it easier to select the correct source (see chapter entitled "Basic settings of the CALA SR").

Volume control

The volume of the CALA SR can be adjusted in fine increments using the - _ + button. A brief press on one volume button increases or reduces the volume by one increment. Holding one of the volume buttons pressed in causes the volume to change continuously.

Switching outputs

Briefly pressing the button switches the speaker outputs on and off.

Tone settings (Tone menu)

The CALASR features a range of facilities for adjusting the sound to suit your personal preferences, the system's location and your room acoustics. All sound settings are grouped together in the tone control menu (TONE menu).

The tone control menu is called up using the button.

The features of the tone control menu are explained in detail in the next section.

	Adjustment range / Options:	Explanations:
Balance	-85 0+85	This menu point allows you to alter the balance between the left and right loud-speakers in order to compensate for an unfavourable listening position.
Loudness	off / on	The CALASR features a volume-dependent tone control (LOUDNESS) which compensates for the frequency-dependent sensitivity of the human ear, and therefore of human hearing, at very low volume levels. This set-up option is used to switch loudness on or off.
Tone Control	off / on	This menu point can be used to disable (bypass) the CALASR's tone controls. To switch off the tone controls, select the "OFF" setting. When the tone controls are switched off, any adjustments you made to the following menu points "BASS" and "TREBLE" have no effect.
Treble	-12 0 +12	This menu point allows you to alter the treble setting.
Mid	-6 0 +6	This menu point allows you to alter the midrange setting.
Bass	-12 0 +12	This menu point allows you to alter the bass setting.
Subwoofer (This menu point only appears if an external sub- woofer is switched on in the System Configuration menu / Loudspeaker menu.)	-15 0 +15	The volume of the subwoofer can be adjusted at this point. Adjust the volume of the subwoofer to suit the acoustic conditions of the listening room, and the volume of the other channels.
Contour Presence	-5 / -4 / / 0 / / +3	The purpose of this menu point is to adjust the Contour filter for the Presence range. This option enables you to improve speech intelligibility in spoken word programmes, documentaries and sport transmissions.

Contour Fundamental tone

-3 / -2 / -1 / 0 /+1/ +2

The purpose of this menu point is to adjust the Contour filter for the fundamental tone. If you prefer a warmer sound image, amplify the fundamental sound (+1 ... +2). For a cooler sound image, or to eliminate resonance effects, the fundamental tone should be reduced (-1 ... -3).

Mode of operation

Stereo / Virtual Surround

The CALASR offers two modes of operation: STEREO and VIRTUAL SURROUND. In contrast to Stereo mode in Virtual Surround mode it is possible to achieve surround effects even without the presence of physical rear loudspeakers.

The mode of operation can be changed by the MODE button. The first press on the MODE button displays the currently selected mode of operation on the front display. Further button-presses toggle between the modes of operation.


Basic settings of the CALA SR

(System Configuration menu)

The System Configuration menu is used for adjusting the general settings of the machine. This menu is described in detail in the following chapter.

Calling up and operating the menu

- To call up the menu press the (sys) button briefly on the remote control handset.
- When the menu is opened, the screen displays the following Select points:



- If you wish to change the selected menu point, first press the OK button, then use the () buttons to alter the value.
- To accept the setting once you have changed the value, press the **OK** button again.
- If you wish to guit without accepting any alteration, press the button at any time.
- Press the (sys) button again to leave the menu.

Menu item Speaker Speaker setup and

room acoustics

Sub-point Speaker LF Shape This menu point opens a sub-menu in which the settings for the loudspeakers can be altered.

In this menu point you can set the loudspeaker type and, if appropriate, the cross-over frequency between the main loudspeakers (loudspeaker group A - left / right) and the sub-woofer.

If you are using large loudspeakers, please choose the "FULL RANGE" setting. For relatively small satellite speakers we suggest that you choose a cross-over frequency of 40Hz, 60Hz, 100Hz or 150Hz, depending on the size and bass performance of your loudspeakers.

This is the basic rule: the smaller the speaker cabinet, the higher the cross-over frequency should be. The "Bass extd." setting is recommended for small loudspeakers such as small bookshelf units, if they are operated without a sub-woofer. At this setting the bass range of the speaker is extended to low frequencies.

Sub-point SPK stand ...

If loudspeakers are set up close to a wall or a corner, the result may be a disproportionate boost to the low frequencies. To compensate for this effect please select one of the set-up options

free / near to wall / in a corner / shelf, according to the location of your loudspeakers.

Sub-point **Room**

The purpose of this menu is to fine-tune the CALASR to match the acoustics of your listening room. For highly damped rooms it is advisable to select one of the "absorptive" settings 1 - 4.

The "reflective" settings 1 - 6 help to reduce any reverberant effects. If your listening room is normally damped, this setting should be left at "normal"

Sub-point **Subwoofer**

In this menu point you can set the cross-over frequency for your sub-woofer. If your system does not include a sub-woofer, you should choose the "OFF" setting.

Sub-point OUT / Phones

In this menu point you can disable the room correction settings for the use of headphones. Choose the setting "phones" to bypass the room correction and choose the setting "OUT" if e.g. active speakers are connected, for which the room correction is eventually required.

Is the setting "phones" selected, the settings for the menu items "Room" (System settings menu) and "Contour presence" and "Contour fundamental tone" (Tone menu) have no effect to the phones- and Analog OUT sockets.

Menu item Source settings

This menu point opens a sub-menu in which the individual sources connected to the **CALASR** can be configured.

1

Not all the set-up options are available for all sources.

Sub-point Available

The purpose of this menu point is to disable / activate the corresponding source.



Disabled sources do not appear in Source Select when you operate the remote control handset, and this makes it easier to select the correct source. It is therefore advisable to disable all sources which you do not use.

Sub-point Source name

At this menu item you can assign a plain text name to each source; this name then appears in the screen displays.

When you call up this menu item using the ok button, a list of all the internal and external sources of the CALA SR appears.

To change the plain-text name, move to the appropriate line and press the <a>oK button. Now use the alpha-numeric keypad of the **FM1000** to change the name as required, then confirm your choice with <a>oK ; this saves the settings for that source.

The button is used to switch between numeric and alpha-numeric input, and between capitals and lower-case letters. Letters can be erased by pressing the button.

If you should wish to restore the factory default source name, erase the whole name before saving the empty field with the **OK** button: this action resets the display to the standard source names.

Sub-point **Auto-power-on**

This menu point enables you to automatically switch on the CALASR due to the automatic power-on function.

If this function is switched on, the CALASR automatically switches itself on from standby mode, and switches to the selected source (if necessary), when a music signal is present at the Analog In 1, Analog In 2 or Digital In 1 - 3 input - depending on the input to which the auto power-on function is assigned.

If the CALASR is switched on, but no signal is detected at the auto power-on input within about twenty minutes, then the CALASR automatically switches itself off again; however this only occurs if the auto power-on source is selected.



The automatic power-on function is only active when the Energy Saver function is disabled.

Sub-point Passthrough

If you wish to connect a device with its own volume control (e.g. TV set), this menu point can be used to disable the volume control of the CALASR for the **Analog In 1** input (pass-through mode).



You should only select this setting if a device with its own volume control is connected to the unit. Ensure that the volume of the source device is turned down to zero before connecting it to the CALASR, otherwise the speakers connected to it may be ruined through overloading.

Sub-point **Phono mode**

The purpose of this menu point is to configure the input **Analog In 2** for connecting a turntable fitted with an MM pick-up.



Never select this setting unless a turntable (without integrated phono preamp – output voltage until 10 mV) is connected to the CALASR, otherwise the speakers connected to the unit may be ruined through overloading.

Sub-point Input level

The input for sources **Analog In 1** and **Analog In 2** can be adjusted to suit the output level of the device connected to these sockets. The input level can be set to any of four values. Set the input in such a way that the volume matches that of the **CALA SR**'s internal sources, then confirm your choice with the **OK** button. This action saves the settings for that source. The input level can be adjusted to any of the settings 500 mV, 1,0 V, 2,0 V or 2,8 V.



If you have configured the source **Analog In 2** for connecting a turntable, this set-up option is used to adjust the input sensitivity to any of the settings 2.5mV, 5mV or 10 mV to suit an MM pick-up.

Menu item Display brightness

Here you can adjust the brightness of the screen in normal use to suit your personal preference. The available settings are: 1 to 7



We recommend that brightness settings 6 and 7 should only be used when the screen is difficult to read due to very bright ambient light. A lower brightness setting will extend the useful life of the screen.

Menu item Display mode

This menu item offers the choice between three different display operation modes:

- Always on
- Temporary
- Always off

Selecting 'Temporary' will switch the display is on for a short while each time the CALASR is being operated. Shortly after operation the display will be switched off again automatically.



To switch the display on again, from the "always off" setting, call up the system settings menu by a brief press on the **878** button.

Menu item Ambient brightness

In this menu point you can set your preferred brightness for the ambient lighting of the CALASR. The brightness can be adjusted to any of ten settings.

Menu item Ambient colour

In this menu point you can switch on and set the preferred colour for the ambient lighting.

Menu item Ambient colour cycling

If you have configured the ambient colour (see menu item above) to the setting "flowing", under this menu item you can adjust the speed the ambient lighting cycles through the different colours in four steps from very slow to fast.

 $|\mathbb{O}|$

This menu item only appears, if under the menu item "Ambient colour" the setting "flowing" is selected.

Menu item Language

In this menu point it is possible to determine the language which is to be used for the displays on the integral screen on the front panel of the CALASR.



The language used for any transferred data, e.g. from an Internet radio station, is determined by the device itself or the radio station, and therefore <u>cannot</u> be selected on the CALASR.

Menu item Device name

This menu point can be used to assign an individual name to the CALASR. In a home network the device then appears under this name.

Menu item Network

All network settings can be carried out at this menu point. For a detailed description on setting up a LAN or WLAN connection please also refer to the section entitled "**Network configuration**".

Menu item Music services

At this point you can enter the access data for the music streaming services (TIDAL etc.) supported by the CALASR.

Calling up this menu point by pressing the **OK** button displays a list of the supported music services.

Select the service you wish to use, then confirm your choice with the ok button.


Now use the alpha-numeric keypad of the **FM1000** to enter the access data which you have received from your service provider in the lines "**User**" and "**Passphrase**".

Use the button to switch between numeric and alpha-numeric input, and between capitals and lower-case letters.

Press the button to erase any letter.

In each case confirm your input of user name and password by pressing the (ok) button.

To conclude the procedure and save the data, select the menu entry "Store and exit?" and confirm by pressing the (K) button.



The music streaming services supported by the CALASR require a subscription to the appropriate service provider.

Menu item Bandwidth limit

This menu point can be used to adjust the link speed of the Internet connection. The bitrate of the Internet radio stations and streaming services is adjusted automatically to match your chosen setting. If you select "no limit" for bandwidth limit, the highest available quality is always selected automatically.



If you do not know the exact bandwidth of the internet connection, we recommend that you select the setting at which no drop-outs occur during playback.

Menu item Energy saver (Stand-by mode)

Default

settings

The CALASR features two stand-by modes: ECO Standby with reduced stand-by current drain, and Comfort Standby with additional functions, but slightly higher current drain. You can select your preferred stand-by mode in this menu point:

On (ECO Standby)

Active functions in ECO Standby mode:

· Can be switched on by remote control

Off (Comfort-Standby)

The following expanded functions are available:

- Can be switched on by remote control
- Can be switched on by App
- Alarm-timer with clock display
- Automatic power on function for inputs Analog In 1, Analog In 2 and Digital In 1 -3.

and restores the machine to the state as delivered (factory defaults).

Device Info menu item	At this menu point you will find information on the status of the installed software and the factory reset.
Sub-point Update	At this point it is possible to initiate a firmware update. The update can be accessed from an Internet connection.
Sub-point Update package	This point displays the currently installed software package.
Sub-point Control	Display of the control software version
Sub-point Client	Display of the Streaming Client software version
Sub-point DAB / FM	Display of the tuner software version.
Sub-point	Calling up and confirming this menu point erases all personal settings,

Alarm Timer

The machine features an integral Timer module which is capable of switching the CALASR on with a selectable source at a programmable time (alarm clock).

Selecting an alarm timer in the Alarm Timer menu switches the function on and activates it. You can now switch the CALASR off. The CALASR will switch itself on at the pre-set time for as long as the set time is displayed on the screen.

①

This function is only possible if the Energy Saver is switched off. Please refer chapter "Basic settings of the CALA SR".

Alarm function - with automatic

power-off

If the Timer is active, the **CALA SR** switches itself on at the programmed alarm time. Once switched on, a bell symbol flashes on the screen.

The CALASR switches itself off automatically one hour after the alarm time, unless the alarm function is disabled during this period.

The alarm function can be disabled by operating or switching off the device. If the alarm function is disabled, the time display and bell disappears. If the timer is disabled by operating the device it now does **not** switch itself off **automatically** after an hour! If you wish to switch the machine off, you must do so manually by pressing the **b** button.

Switching the Timer off

A long press on the **SYS** button calls up the Alarm Timer menu, where the timer can then be disabled.



A long press on the **SYS** button calls up the Alarm Timer menu even when the machine is switched off.

Quick selection menu

A alarm timer set in the alarm timer menu can be selected comfortably, quick and without switching on the device, by using the quick selection menu.

A brief press on the we button calls up the quick selection menu. Further button presses, repeatedly if necessary, select the desired alarm timer. The alarm time of the selected timer can be adjusted by pressing the buttons and the volume can be set by pressing the buttons.

A brief press on the () button enables the selected alarm timer.

Alarm Timer menu

Calling up and operating the menu

- A long press on the (sys) button calls up the menu.
- When you open the menu, you will hear the currently set alarm source at the currently set alarm volume.

The screen displays the following Select points:



- If you wish to change a selected menu point, first press the OK button, and then use the / D buttons to alter the value.
- To accept the setting once you have altered the value, press the ok button again.
- If you wish to quit without accepting an alteration you have made, press the button at any time.
- Press the (sys) button again to leave the menu.

Menu item Alarm

In this menu point you can select whether the machine is to be switched on automatically, and using which alarm.

Menu item Alarm Time

Manual alarm time setting for the currently active alarm. Any change you make at this point takes place slowly at first; holding the button pressed in increases the rate of change.

Menu item Alarm Source

in increases the rate of change.

Selects the source which is to be switched on at the alarm time point.

If you select the menu point Radio, you can use the buttons to select a radio station from the Favourites list.



Waking to the radio:

Take care to set a station which can be received well.

Menu item Alarm Vol.

You can set the alarm volume at this point. If you change the volume setting, the system immediately accepts the displayed volume level, and the change in volume is audible.

Menu item Time Mode

This menu point is used to determine how the internal clock is set.

FM / DAB: If you select the menu point FM or DAB, you can select a radio station from the Favourites list using the ______ / ____ buttons. If a station is selected, the time of day is automatically read out from the RDS signal at night. If the selected station is the current listening source, then the time of day is also taken from the machine when it is switched on. This only works if a good RDS signal can be received. It is not possible to adjust the time of day manually!

Summer time: The time of day can be set manually in the menu point 'Set time'.

Winter time: The time of day can be set manually in the menu point 'Set time'

Menu item Set Time

Manual method of setting the internal clock to the correct time. Any change you make at this point occurs slowly at first - holding the button pressed in increases the rate of change.

①|!

Manual adjustment is only possible if you have set Summer or Winter in the menu point 'Clock mode'.

Menu item Time display

At this point the time format can be set to 12 hour (AM / PM) or 24 hour format.

Menu item Show clock

At this point you can choose whether the time of day is displayed in standby operation.

Menu item Brightness Clock

At this point you can adjust the screen brightness in Stand-by mode to suit your personal preference. The brightness setting becomes active immediately.



This menu item appears only if the clock is displayed in standby operation. See menu item above.

Slumber-function

The machine has a slumber function that switches it to standby after a selectable time interval between 15 minutes and 12 hours. This selection can be done in steps of 15 minutes.

Activate slumber function

While the **CALASR** is powered up keep the **6** key of the remote control pressed until the display shows the slumber time.

Change the slumber time

While the slumber function is active the slumber time can be modified in steps of 15 minutes using the / -keys. Any change comes immediately into effect.

Turn off slumber function

While the slumber function is active it can be turned off by keeping the **b** key pressed until the displaying of the slumber time is not shown any longer on the display. After switching the function off the device can be operated in the usual way. Alternatively the slumber function is also ended when the **CALA SR** is switched off



As long as the slumber function is active there is no other user operation possible besides the slumber functions mentioned above and the changing of the volume.

Operating the sources in detail

Favourites lists

General information

The CALASR includes the facility to create Favourites lists. The purpose of these lists is to store radio stations and podcasts, so that they can be accessed swiftly.

Each of the sources **FM radio**, **DAB radio**, and **Internet radio** (incl. podcasts) features its own Favourites list.

Once stored, the favourites can either be selected from the Favourites list, or called up directly by entering the program location number. The option of selecting using the location number is particularly useful when you wish to call up favourites when the screen is not in view (e.g. from an adjacent room) or using a house control system.




Favourites lists for the various music services (TIDAL etc.) are not supported.

Instead it is usually possible to add Favourites and Playlists on-line via the provider's account. These can then be called up and played via the CALASR

Calling up the Favourites list

- The first step is to switch to one of the sources listed above.
- Press the 🔳 button to call up the Favourites list.



- Here the program location number is displayed within the list. Since it is possible to erase individual list items, the numbering may not be continuous.
- b) The selected list entry is displayed in enlarged form.
- c) Position display in the Favourites list.

Adding a favourite

If you especially enjoy the piece of music or radio station to which you are currently listening, simply press the green button on the FM1000; this action stores the station in the corresponding Favourites list



Each Favourites lists features 99 program locations. Favourites lists can only be used to store the piece of music and station which is currently playing.

Erasing a favourite from the Favourites list

Open the Favourites list by pressing the button. Use the buttons to select the station in the list which you wish to erase, then hold the red button pressed in; this action removes the item from the Favourites list.

①

Erasing a Favourite does not cause the following Favourites to move up the list. The station position is no longer displayed after erasure, but a new Favourite can still be assigned to it.

Selecting a favourite from the list

- Press the button to call up the Favourites list.
- Select the favourite to be played by pressing the or button.
- You can return to the station to which you are currently listening (quit) by pressing the button.

Directly selecting a favourite

In addition to the option of selecting favourites using the Favourites list, it is possible to access the desired favourite directly by entering the program location number.

After you have pressed the numeric buttons, playback switches to the favourite you have just selected.

Sorting Favourites lists

The sequence of items in the Favourites list you have created can be altered in any way you wish. This is the procedure for changing the order of the list:

- The first step is to call up the Favourites list by briefly pressing the button.
- Pressing the button activates the Sort function for the selected favourite. The favourite is highlighted on the screen.



- Now move the activated favourite to your preferred position in the Favourites list.
- A further press on the button de-activates the Sort function, and the favourite is stored at the new position.

Briefly press the button again to close the Favourites list.



If you have previously erased a number of favourites, you may well find that some program locations in the Favourites list are missing (empty). Nevertheless, the favourites can still be moved to any location in the list!

Operating the radio


The CALASR features an FM tuner (VHF radio), a DAB+ receiving section (digital radio) and also includes the facility to stream Internet radio. The following section describes in detail how to operate the individual radio sources.

FM - Radio

Selecting FM radio

Briefly tap the (RADIO) button on the FM1000 remote control handset, repeatedly if necessary, until the source "FM Radio" is displayed on the screen.

General



- a) Displays the type of reception currently in use.
- b) Hear the music type or style is displayed, e.g. Pop Music.
- c) This information is only displayed if the transmitting station broadcasts it as part of the RDS system. If you are listening to a station which does not support the RDS system, or only supports it in part, these information fields remain empty.
- d) The frequency and / or the station name is displayed in enlarged form. If a station name is displayed, its frequency is shown in area 'e'.
- e) These lines display information which is broadcast by the station (e.g. Radio text).
- f) Display of Stereo '**™**' / Mono "**®**"

The *field strength* \P^3 and therefore the reception quality to be expected from the set transmitting station can be assessed from the field strength.

Manual station search

Holding one of the 4 / b buttons pressed in initiates a station search for FM tuner in the upward or downward direction. The station search stops automatically at the next station. A frequency can be selected directly by pressing the 4 / b buttons repeatedly. Briefly pressing the 4 / b buttons on the **FM1000**, repeatedly if necessary, enables you to select a particular frequency.

As soon as the station is audible, you can add it to your Favourites list by pressing the () button.


Automatic station search

A brief press on the **Sec** button to calls up the Station list menu. The following Select points are available:



- If you wish to create a new station list, select the item "Create new list" and confirm your choice with OK.
- The station search begins, and automatically searches for all radio stations which the machine is able to pick up.
- If you wish to update an existing list, select the item "Add new stations".
- The menu item "Sort stations by ..." allows you to sort the stored list by any of several criteria.

Selecting a station from the Station list



a) Use the ____ / ___ buttons to select one of the stored stations. The station you choose is now displayed in enlarged form.

Press the or ok button to select the enlarged station for playing.

Pressing the button returns you to the station to which you are currently listening (quit).

- b) Position indicator in the Favourites list.
- Stations to which you often listen can be stored in a Favourites list; this makes it easier to select them (see the section entitled "Favourites list").

RDS functions

- If the station being received is broadcasting relevant RDS data, the following information will be displayed on the screen:
 - Station name
 - Radio text
 - Program type (genre)

For stations that do not support the RDS system or only partially or with weak reception, no information will be displayed.

Switching Radio Text on and off

The Radio text function can be switched on and off by briefly pressing the button on the remote control handset.

Mono / Stereo (only FM – Radio)

You can toggle the radio of the **CALA SR** between stereo and mono reception by briefly pressing the **1** button. The reception mode is shown on the screen by the following symbols:

'●' (Mono) or '**™**' (Stereo)

If the station you wish to listen to is very weak or very distant, and can only be picked up with severe background noise, you should always switch to MONO mode as this reduces the unwanted hiss significantly.

The Mono and Stereo symbols are only shown in the detailed screen display.


DAB - Radio

Selecting DAB radio

Briefly tap the **RADIO** button on the **FM1000** remote control handset, repeatedly if necessary, until the source "**DAB Radio**" is displayed on the screen.

Depending on the frequency band (block), it may take up to two seconds to switch stations when in **DAB mode**.

Display




- a) Displays the type of reception currently in use.
- b) Hear the music type or style is displayed, e.g. Pop Music. This information is only displayed if the transmitting station broadcasts it as part of the RDS system. If you are listening to a station which does not support the RDS system, or only supports it in part, these information fields remain empty.
- c) The frequency and / or the station name is displayed in enlarged form. If a station name is displayed, its frequency is shown in area 'e'.

- These lines display information which is broadcast by the station (e.g. Radio text).
- e) Display of Stereo 'op'.
- f) The *field strength* (q) and therefore the reception quality to be expected from the set transmitting station can be assessed from the field strength.
- g) Bit-rate of the broadcasting station when listening to DAB radio.

Automatic station search


A brief press on the **SRC** button to calls up the Station list menu. The following Select points are available:



- If you wish to create a new station list, select the item "Create new list" and confirm your choice with ok.
- The station search begins, and automatically searches for all radio stations which the machine is able to pick up.
- If you wish to update an existing list, select the item "Add new stations".
- The menu item "**Sort stations by** ..." allows you to sort the stored list by any of several criteria.

Selecting a station from the Station list

 Pressing the / buttons opens the list of all stored stations.



- a) Use the ____ / ___ buttons to select one of the stored stations. The station you choose is now displayed in enlarged form. Press the ____ or ___ button to select the enlarged station for playing.
 - Pressing the button returns you to the station to which you are currently listening (quit).
- b) Position indicator in the Favourites list.
- Stations to which you often listen can be stored in a Favourites list; this makes it easier to select them (see the section entitled "Favourites list").

The higher the bit-rate, the better the station's sound quality.

RDS functions

If the station being received is broadcasting relevant RDS data, the following information will be displayed on the screen:

- Station name
- Radio text
- Program type (genre)

For stations that do not support the RDS system or only partially or with weak reception, no information will be displayed.

Internet-Radio

Selecting Internet Radio as source

Briefly tap the (RADIO) button on the **FM1000** remote control handset, repeatedly if necessary, until the source "**Internet**" is displayed on the screen.

Selecting podcasts


Select the "Podcasts" entry instead of the "Radios" entry from the list using the buttons, and confirm your choice with or K.



The method of operating music services is described separately in the section entitled "Operating music services".

Playback

The music content to be played is selected with the help of Select lists. These lists are controlled using the navigation buttons (cursor buttons) on the remote control handset.



	a)	Use the / buttons to select the desired entry from the list.
		A brief press selects the previous / next entry within the list. The scrolling speed can be increased by holding the button pressed.
		The list entry you choose is now displayed in enlarged form.
		Press the or ok button to open or start the list entry shown in enlarged form.
		Pressing the button returns you to the previous folder level.
	b)	Indicates the currently selected point within the opened list.
	Pres	rting playback ss the button on the remote control handset or the machine's t panel to start playback.
		pping playback ssing the button halts playback.
	Fav	ions and podcasts to which you often listen can be stored in a ourites list; this makes it easier to select them (see the section tled "Favourites list").
		Search function provides a means of locating Internet radio stations
	•	is is the procedure for searching for a particular Internet radio station: Locate the Select list for the entry "Radio", then use the / buttons to select the "Search" item, and confirm your choice by pressing the button or while navigating within lists alternatively call up the search function by pressing the blue
		You will now see a window in which you can enter the keyword using the remote control handset's alpha-numeric keypad.
	•	Press the button to erase any letter.
	•	Briefly press the ox button to start the search.
	•	After a short delay you will see a list of the search results.
D	l .	search function can be called up from every point within the lists by ssing the blue button.
	pos	search strings can consist of up to eight characters. It is also sible to enter multiple keywords separated by a space character, e.g. C Rad".

To search for a podcast, select the "Search" entry under "Podcasts".

Favourites lists

Search function

Operating music services

General information

The Cala supports playback of music services such as TIDAL.

To make use of music services you may need to take out a paid subscription with the appropriate provider.

Use of music services requires the input of access data (username and password. These access data can be stored separately for each provider in the "Music services" menu within the System Configuration menu (see the section entitled "Basic settings of the CALA SR").



Future music services and others which are not currently supported may be added subsequently by updates to the firmware of the CALASR.


Selecting the music service

Press the **RADIO** button on the **FM1000**, repeatedly if necessary, to select Internet radio as source.

Once Internet radio is set as the source, a list appears which contains all the available music services as well as Internet radio. To select a service, use the / v buttons to navigate to the appropriate line. Pressing the v button opens the Select list for the corresponding service.

Playback

The music content to be played is selected with the help of Select lists. These lists are controlled using the navigation buttons (cursor buttons) on the remote control handset.



A brief press selects the previous / next entry within the list. The scrolling speed can be increased by holding the button pressed.

The list entry you choose is now displayed in enlarged form.

Press the or or ow button to open or start the list entry shown in enlarged form.

Pressing the (button returns you to the previous folder level.

b) Indicates the currently selected point within the opened list.

Starting playback

Press the button on the remote control handset to start playback.

Stopping playback

Pressing the button halts playback.

Skipping tracks

A brief press on the () buttons during playback causes the device to jump to the next or previous piece of music within the current playlist.



The exact form of the displayed list and the preparation of the content depend to a large extent on the music service provider. You may therefore find that in some cases not all the functions described in these instructions can be used.

Search function

In order to find quickly what you want in the wide range of services on offer, it is possible to search for specific items in the content available from music service providers.

The first step in the procedure is to open the Select list of the appropriate music service. Navigate to the "Search" entry, and confirm by pressing the ok button. As an alternative it is possible to call up the search function by pressing the blue button while navigating in lists.

A window now opens in which the keyword can be entered using the remote control handset's alpha-numeric keypad.

Press the button to erase any letter.

Start the search by briefly pressing the **OK** button.

After a short delay a list appears showing the search results.

The results list varies from one music service to another. Many services allow you to filter the search results by artiste, album or track once the search has been completed.



The search function can be called up from every point within the lists by pressing the blue button.



The search strings can consist of up to eight characters. It is also possible to enter multiple keywords separated by a space character, e.g. "The Beat".

Playlists and favourites

Most music services offer the facility to register on the provider's website with the user data, create dedicated playlists, and manage the lists conveniently.

Once created, the playlists appear in the Select list of the corresponding music service, where they can be called up and played via the *Cula*.

The location within the select list at which the playlists can be accessed varies from one music service to another. Often these folders are named "My music", "Library", "Favourites" or similar.

Operating the SCL source

(Streaming Client)

General information on the streaming client

The CALA SR features what is known as a 'streaming client'. This facility makes it possible to play music files stored on PCs or servers (NAS) within the network.


The media content formats which the CALASR can reproduce are very wide-ranging, and extend from compressed formats such as MP3, AAC and OGG Vorbis to high-quality non-compressed data formats such as FLAC, ALAC, AIFF and WAV, which are thoroughly audiophile in nature. A full listing of all possible data and playlist formats is included in the Specification, which you will find in the Appendix to these instructions. Since virtually no read or data errors occur when electronic memory media are accessed, the potential reproduction quality is even higher than that of CD. The quality level may even exceed that of SACD and DVD-Audio.

Selecting the SCL source

Briefly tap the **@CL/USB** button on the **FM1000** remote control handset, repeatedly if necessary, until the source "**SCL**" is displayed on the screen.

Playback

The music content to be played is selected with the help of Select lists. These lists are controlled using the navigation buttons (cursor buttons) on the remote control handset.



a) Use the ____ / ___ buttons to select the desired entry Server / Folder / Track from the list.

A brief press selects the previous / next entry within the list. The scrolling speed can be increased by holding the button pressed.

The list entry you choose is now displayed in enlarged form.

Press the or ok button to open or start the list entry shown in enlarged form.

Pressing the (button returns you to the previous folder level.

b) Indicates the currently selected point within the opened list.



The exact form of the displayed list and the preparation of the content also depend to a large extent on the capabilities of the server, i.e. the full facilities of the CALA SR cannot be exploited with all servers or media. You may therefore find that in many cases not all the functions described in these instructions can be used.

Starting playback

Press the **I** button on the remote control handset or the machine's front panel to start playback.

Stopping playback


Pressing the button halts playback.

Skipping tracks

A brief press on the [I buttons during playback causes the device to jump to the next or previous piece of music within the current playlist.

Playback of directories

In addition to the facility to play back individual folder content, it is also possible to play back entire directories. This is accomplished by selecting the folder of the directory to be played, then pressing the button to start playback. Playback commences with the first entry in the list of content to be played. If an entry in the list of content to be played. If an entry in the list should contain a folder with additional subfolders, the content of the lowest folder is always played first. This is followed by the content of the next higher folder level, etc. (see diagram right).



Search function

In order to find quickly what you want in the wide range of services on offer, it is possible to search for specific items in the content available from music service providers.

The first step in the procedure is to open the Select list of the appropriate music service. Navigate to the "Search" entry, and confirm by pressing the ok button. As an alternative it is possible to call up the search function by pressing the blue button while navigating in lists.

A window now opens in which the keyword can be entered using the remote control handset's alpha-numeric keypad.

Press the button to erase any letter.

Start the search by briefly pressing the **ok** button.

After a short delay a list appears showing the search results.

The results list varies from one music service to another. Many services allow you to filter the search results by artiste, album or track once the search has been completed.

The function searches only the current folder. Eventually existing subfolders are ignored.

Playing USB memory media (USB Media source)

General information

The CALASR is capable of playing music files stored on USB memory media, and features an USB socket for this purpose: **USB** on the back panel.



The memory medium can be formatted with any of the following file systems:

FAT16, FAT32, NTFS, ext2, ext3 or ext4.

It is also possible to power the USB memory medium via the USB socket, provided that the unit's current drain accords with the USB norm. Normed 2.5 inch USB hard discs can be connected to the socket directly, without requiring their own mains PSU.


Selecting USB Media as source

Press once or twice on the ©CL/USB button in order to select "USB MEDIA" as source.

All USB memory media connected to the machine are now displayed. If no USB memory medium is found, the screen displays the message "No USB media available".

Playback

The music content to be played is selected with the help of Select lists. These lists are controlled using the navigation buttons (cursor buttons) on the remote control handset.



a) Use the buttons to select an (a) USB memory / folder / track from the list.

A brief press selects the previous / next entry within the list. The scrolling speed can be increased by holding the button pressed.

The list entry you choose is now displayed in enlarged form.

Press the or or button to open or start the list entry shown in enlarged form.

Pressing the button returns you to the previous folder level.

Indicates the currently selected point within the opened list.

Starting playback

Press the button on the remote control handset to start playback.

Stopping playback


Pressing the button halts playback.

Skipping tracks

A brief press on the [] buttons during playback causes the device to jump to the next or previous piece of music within the current playlist.

Playback of directories

In addition to the facility to play back individual folder content, it is also possible to play back entire directories. This is accomplished by selecting the folder of the directory to be played, then pressing the limit button to start playback. Playback commences with the first entry in the list of content to be played. If an entry in the list should contain a folder with additional subfolders, the content of the lowest folder is always played first. This is followed by the content of the next higher folder level, etc. (see diagram right).



Search function

In order to find quickly what you want in the wide range of services on offer, it is possible to search for specific items in the content available from music service providers.

The first step in the procedure is to open the Select list of the appropriate music service. Navigate to the "Search" entry, and confirm by pressing the <a>OK button. As an alternative it is possible to call up the search function by pressing the blue <a>OK button while navigating in lists.

A window now opens in which the keyword can be entered using the remote control handset's alpha-numeric keypad.

Press the button to erase any letter.

Start the search by briefly pressing the **ok** button.

After a short delay a list appears showing the search results.

The results list varies from one music service to another. Many services allow you to filter the search results by artiste, album or track once the search has been completed.

If the text searched for is not found the best matching result will be shown. You can abort the search using the _____-button.

The function searches only the current folder. Eventually existing subfolders are ignored.

Operating the Bluetooth Receiver

The CALASR's integral Bluetooth interface provides a means of transferring music wirelessly from devices such as smart-phones, tablet PCs, iPods, etc. to the Cala.



For a successful audio Bluetooth transfer from a mobile device to the CALASR the mobile device must support the A2DP Bluetooth audio transfer protocol.

Selecting Bluetooth

Select **Bluetooth** as source by pressing the **BT** - button on the remote control handset.

The machine's integral screen now displays **Bluetooth** as source.

Setting up audio transfer

Before music from a Bluetooth-capable device can be played through the CALASR, the external device must first be registered to the CALASR. As long as the CALASR is switched on and no device is connected, it is always ready to receive. In this state the screen displays the message 'not connected'.

This is the procedure for establishing a connection:

- Start a search for Bluetooth equipment on your mobile device.
- When it finds the CALASR, make the connection to your mobile device.

Once the connection is successfully established, the message on the CALASR's screen switches to 'connected to YOUR DEVICE'.



If your device requests a PIN code, this is always '0000'.



Due to the large number of different equipment on the market, we are only able to provide a general description for setting up the radio connection. For detailed information please refer to the operating instructions supplied with your device.

Playback functions

Information on the piece of music being played is displayed on the integral screen of the connected mobile device. If possible we recommend that you leave the screen backlight switched on permanently to ensure that it is clearly legible.

Some Bluetooth devices which support the AVRCP protocol can be controlled by CALA SR's FM1000 remote control handset.

The behaviour and method of operating the connected mobile device are determined by the device itself. In general terms the function of the buttons the FM1000 remote control handset are as follows:

Start and pause playback

The button on the remote control handset is used to start and pause playback (PLAY / PAUSE function).

Stop playback Switch track

Pressing the button halts playback.

Switch track

A brief press on the () / () buttons during playback causes the device to jump to the next or previous piece of music within the current playlist.



Please note that many AVRCP-capable mobile devices do not support the controlling through the **CALASR**. In case of doubt, please ask the manufacturer of your mobile device.

Volume adjustment

To achieve the best possible playback quality, you should only adjust the volume on the CALASR itself: set the playback volume as high as possible on your mobile device, but not so high that the signal is distorted.

Any further changes to volume should then be made using the (vol.+)/(vol.+) button on the FM1000.

Notes



The CALA SR has been tested with a large number of Bluetooth-capable mobile devices. However, we are unable to guarantee general compatibility with all devices available commercially since the range of equipment is so wide, and the various implementations of the Bluetooth standard differ widely in some cases. If you encounter a problem with Bluetooth transfer, please contact the manufacturer of the mobile device.

The maximum range of a Bluetooth audio transfer is normally about 3 to 5 metres, but the effective range may be affected by a number of factors. To achieve good range and interference-free reception there should be no obstacles or persons between the **CALASR** and the mobile device.

Bluetooth audio transfers take place in what is known as the "everyman frequency band", in which many different radio transmitters operate - including WLAN, garage door openers, baby intercoms, weather stations, etc. Radio interference caused by these other services may cause brief dropouts or - in rare cases - even failure of the connection, and such problems cannot be excluded. If problems of this kind occur frequently in your environment, we recommend that you use the Streaming Client or the USB input of the CALASR instead of Bluetooth.

By their nature, Bluetooth transmissions always involve data reduction, and the attainable sound quality varies according to the mobile device in use, and the format of the music to be played. As a basic rule the maximum quality of music which is already stored in a data-reduced format, such as MP3, AAC, WMA or OGG-Vorbis, is worse than with uncompressed formats such as WAV or FLAC. For the highest reproduction quality we always recommend the use of the Streaming Client or the USB input of the CALA SR instead of Bluetooth.

The Cala as D/A Converter

General Information on D/A Converter Operation

The **T-A** CALASR can be used as a high-quality D/A converter for other devices such as computers, digital radios etc. which are fitted with poorquality converters or no converter at all. The CALASR features two optical and one electrical S/P-DIF digital input on the back panel to allow this usage.



You can connect devices with electrical co-axial or optical light-pipe output to the digital inputs of the CALA SR. At the optical inputs DIG 1 and DIG 2 the CALA SR accepts digital stereo signals conforming to the S/P-DIF norm, with sampling rates of 32 to 96 kHz. At the electrical co-axial input DIG 3 the range of sampling rates is from 32 to 192 kHz.

D/A Converter Operation

Selecting a D/A Converter Source

Choose the digital input to which you have already connected the source device which is to be played by pressing the **DIN** button on the **FM1000** (repeatedly if necessary).

As soon as the source device delivers digital music data, the CALASR automatically adjusts itself to the format and sampling rate of the signal, and you will hear the music.

Front panel display




During D/A converter operations the CALASR integral screen displays the characteristics of the digital input signal.

Installation, Using the system for the first time, Safety notes

This section describes all those matters which are of fundamental importance when setting up and first using the equipment. This information is not relevant in daily use, but you should nevertheless read and note it before using the equipment for the first time.

Back panel connections



Mains input	The mains lead is plugged into this socket. For information on correct mains connections please refer to the notes in the Chapters 'Using the system for the first time', 'Wiring' and 'Safety Notes'.
ANT (Aerial input)	The CALASR features a 75 Ω aerial input marked ANT which is suitable for a cable connection as well as a standard domestic radio aerial. For first-class reception quality a high-performance aerial system, competently installed, is a fundamental necessity.
Digital DIG 1 Digital DIG 2	Inputs for digital source devices with an optical digital output. At these inputs the CALASR accepts digital stereo signals conforming to the S/P-DIF norm, with sampling rates of 32 to 96 kHz.
	These inputs are equipped with an automatic power on function. Please refer chapter 'System settings / source settings'
Digital DIG 3	Input for digital source devices with a co axial digital output. At this input the CALASR accepts digital stereo signals conforming to the S/P-DIF norm, with sampling rates of 32 to 192 kHz. This input is equipped with an automatic power on function. Please refer chapter 'System settings / source settings'
Digital OUT	
Digital OUT	At this socket is the signal from the chosen source available. It can be transmitted to e.g. a digital recorder.
	It is not possible to produce a digital version of all played media, as in some cases the original contains copyright protection.
GND	The ground lead from an analogue record player is connected here

in order to avoid hum.

Analog IN 1 / IN 2

Universal analogue stereo sound input

- These inputs are equipped with an automatic power on function. Please refer chapter 'System settings / source settings'
- In the System Configuration menu it is possible to configure the input **IN 2** as input for an analogue turntable (pick-up).

Analog OUT (A)

Analogue audio output (Pre Out), typically for connecting active loudspeakers or headphones.

The level of this output is variable; the level is controlled in parallel with the loudspeaker outputs.

A 3.5 mm barrel socket Ω is available, wired in parallel with the Cinch / RCA output, for connecting headphones. The function of the two outputs is identical.



\triangle

The use of headphones

Continuous listening to programme material via earphones or head-phones at very high volume can result in permanent hearing loss. You can avoid damaging your health by not listening via headphones or ear-phones at high levels for long periods.

SUB OUT

Output socket for an active sub-woofer.

The use of a sub-woofer is optional.



If a sub-woofer is connected, it must be switched on in the Loudspeaker menu (see Chapter 'System Settings, Loudspeaker').

USB

Socket for a USB memory stick or external hard disc

The storage medium can be formatted with the FAT16, FAT32, NTFS, ext2, ext3 or ext4 file system.

The USB storage medium can be powered directly via the USB port provided that its current drain is in accordance with the USB norm. Normalised 2.5" USB hard discs can be connected directly, i.e. without a separate mains PSU.

LAN


Router socket



If LAN is connected, the LAN connection has priority, and WLAN is automatically disabled.

WLAN

Input socket for WLAN antenna



* The aerial can also be set up free-standing using the magnetic base supplied in the set; this ensures maximum possible range.

①

Automatic Activation of the WLAN Module

After powering on the **MP 2000** R detects if it is connected to a wired LAN Network. If no wired LAN connection is found, the **MP 2000** R will automatically activate its WLAN module and it will try to get access to your WLAN network



Attention!

When WLAN shall be used, the LAN socket must be left unconnected.

One pair of loudspeakers can be connected to the \square (SPEAKER \triangleleft R and SPEAKER \triangleleft L). The impedance of each speaker must not be lower than 4 Ω (DIN rating).



Attention!

The load capacity of the loudspeakers connected to the device must be appropriate to the amplifier. The speaker impedance must be at least 4 Ohm (DIN rating). Always connect your loudspeakers using ready-made, purpose-designed speaker cables terminating in approved connectors. The speaker cables and connectors must be insulated in accordance with regulations, and the conductors must have a minimum cross-sectional area of 1.5 mm². The output stages are designed to cope with a minimum load of $2\,\Omega_{\rm h}$ but continuous operation at very high volume produces high currents in the power output stages which can lead to overheating. This in turn trips the protective circuit which switches the amplifier off automatically. Make sure that the terminals are firmly screwed down, and that no short-circuits are possible.



If the loudspeakers are to be used in countries outside the EU the red/black stoppers can be removed from the loudspeaker terminals. The speakers can then be connected using banana plugs.

The stoppers are simply a push-fit in the terminals, and can be prised out from the rear using a suitable tool such as a knife blade.

Installation and wiring

Carefully unpack the unit and store the original packing material carefully. The carton and packing are specially designed for this unit and will be needed again if you wish to move the equipment at any time

If you have to transport the device, it must always be carried or sent in its original packaging in order to prevent damage and defects.

If the unit gets very cold (e. g. when being transported), condensation may form inside it. Please do not switch it on until it has had plenty of time to warm up to room temperature, so that any condensation evaporates completely.

If the device has been in storage, or has not been used for a protracted period (> two years), it is essential to have it checked by a specialist technician before re-use.

Before placing the unit on sensitive laquer or wood surfaces please check the compatibility of the surface and the unit's feet on a non visible point and if necessary use an underlay. We recommend a surface of stone, glass, metal or the like.

The unit should be placed on a rigid, level base (See also chapter "Safety notes"). When placing the unit on resonance absorbers or anti-resonant components make sure that the stability of the unit is not reduced.

The unit should be set up in a well ventilated dry site, out of direct sunlight and away from radiators.

The unit must not be located close to heat-producing objects or devices, or anything which is heat-sensitive or highly flammable.

Mains and loudspeaker cables, and also remote control leads must be kept as far away as possible from signal leads and antenna cables. Never run them over or under the unit.

① |

Notes on connections:

A complete connection diagram is shown in 'Appendix A'.

- Be sure to push all plugs firmly into their sockets. Loose connections can cause hum and other unwanted noises.
- When you connect the output sockets of the source device to the input sockets of the CALASR always connect like to like, i. e. 'R' to 'R' and 'L' to 'L'. If you fail to heed this then the stereo channels will be reversed.
- The device is intended to be connected to mains outlet with protective earth connector. Please connect it only with the mains cable supplied to a properly installed mains outlet with protective earth connector.
- To achieve maximum possible interference rejection the mains plug should be connected to the mains socket in such a way that phase is connected to the mains socket contact marked with a dot (●). The phase of the mains socket can be determined using a special meter. If you are not sure about this, please ask your specialist dealer.

If you encounter problems when setting up and using the amplifier for the first time please remember that the cause is often simple, and equally simple to eliminate. Please refer to the section of these instructions entitled 'Trouble shooting'.

Loudspeaker and signal cables


Loudspeaker cables and signal cables (inter-connects) have a significant influence on the overall reproduction quality of your sound system, and their importance should not be under-estimated. For this reason **T-A** recommends the use of high-quality cables and connectors.

Our accessory range includes a series of excellent cables and connectors whose properties are carefully matched to our speakers and electronic units, and which harmonise outstandingly well with them.

For difficult and cramped situations the **T+A** range also includes special-length cables and special-purpose connectors (e. g. right-angled versions) which can be used to solve almost any problem concerning connections and system location.

Changing the batteries

Locate the point indicated by the arrow in the left picture, and open the battery compartment by pressing it in and simultaneously sliding back the battery cover. Insert three batteries of the LR 03 (MICRO) type in the battery compartment, as shown in the engraved diagram. Please note: it is essential to replace all three batteries at the same time.



\triangle

Caution!

Batteries shout not be exposed to excessive heat like sunshine, fire or the like.



Disposing of exhausted batteries:

Exhausted batteries must never be thrown into the household waste! They should be returned to the battery vendor (specialist dealer) or your local toxic waste collection point, so that they can be recycled or disposed in a proper way. Most local authorities provide collection centres for such waste, and some provide pick-up vehicles for old batteries.

Care of the unit

Disconnect the mains plug at the wall socket before cleaning the case. The surfaces of the case should be wiped clean with a soft, dry cloth only.

Never use solvent-based or abrasive cleaners!

Before switching the unit on again, check that there are no short-circuits at the connections, and that all cables are plugged in correctly.

Storing the unit

If the device has to be stored, place it in its original packaging and store it in a dry, frost-free location. Storage temperature range 0...40 $^{\circ}\text{C}$

Safety notes

For your own safety please consider it essential to read these operating instructions right through, and observe in particular the notes regarding setting up, operation and safety.

Installation

Please consider the weight of the device. Never place the device on an unstable surface; the machine could fall off, causing serious or even fatal injury. Many injuries, especially to children, can be avoided if the following simple safety precautions are observed:

- Use only such items of furniture which can safely bear the weight of the device.
- Ensure that the device does not project beyond the edges of the supporting furniture.
- Do not place the device on tall furniture (e.g. bookshelves) without securely anchoring both items, i.e. furniture and device.
- Explain to children the hazards involved in climbing on furniture to reach the device or its controls.

When installing the unit on a shelf or in a cupboard it is essential to provide an adequate flow of cooling air, to ensure that the heat produced by the unit is dissipated effectively. Any heat build-up will shorten the life of the unit and could be a source of danger. Be sure to leave free space of 10 cm around the unit for ventilation.

If the system components are to be stacked then the amplifier must be the top unit. Do not place any object on the top cover.

The unit must be set up in such a way that none of the connections can be touched directly (especially by children). Be sure to observe the notes and information in the section 'Installation and Wiring'.

Power supply

The device is intended to be connected to mains outlet with protective earth connector. Please connect it only with the mains cable supplied to a properly installed mains outlet with protective earth connector.

The power supply required for this unit is printed on the mains supply socket. The unit must never be connected to a power supply which does not meet these specifications. If the unit is not to be used for a long period disconnect it from the mains supply at the wall socket.

Mains leads / Mains plug

Mains leads must be deployed in such a way that there is no danger of damage to them (e. g. through persons treading on them or from furniture). Take particular care with plugs, distribution panels and connections at the device.

Unplugging the mains plug will disconnect the device from the mains for service and repair. Please make sure that the mains plug is easily accessible.

Enclosure openings

Liquid or particles must never be allowed to get inside the unit through the ventilation slots. Mains voltage is present inside the unit, and any electric shock could cause serious injury or death. Never exert undue force on mains connectors.

Protect the unit from drips and splashes of water; never place flower vases or fluid containers on the unit.

Do not place naked flame sources, such as candle lights on the device.

Supervision of device operation

Like any other electrical appliance this device should never be used without proper supervision. Take care to keep the unit out of the reach of small children.

Service, Damage

The case should only be opened by a qualified specialist technician. Repairs and fuse replacements should be entrusted to an authorised **T+A** specialist workshop. With the exception of the connections and measures described in these instructions, no work of any kind may be carried out on the device by unqualified persons.

If the unit is damaged, or if you suspect that it is not functioning correctly, immediately disconnect the mains plug at the wall socket, and ask an authorised **T+A** specialist workshop to check it.

Approved usage

The device is designed to operate in a temperate climate and altitudes up to 2000 m above sea level. The range of permissible operating temperatures is +10 ... +35°C.

This device is designed exclusively for reproducing sound and/or pictures in the domestic environment. It is to be used in a dry indoor room which meets all the recommendations stated in these instructions.

Where the equipment is to be used for other purposes, especially in the medical field or any field in which safety is an issue, it is essential to establish the unit's suitability for this purpose with the manufacturer, and to obtain prior written approval for this usage.

Over voltage

The unit may be damaged by excess voltage in the power supply, the mains circuit or in aerial systems, as may occur during thunderstorms (lightning strikes) or due to static discharges.

Special power supply units and excess voltage protectors such as the **T+A 'Power Bar'** mains distribution panel offer some degree of protection from damage to equipment due to the hazards described above.

However, if you require absolute security from damage due to excess voltage, the only solution is to disconnect the unit from the mains power supply and any aerial systems.

To avoid the risk of damage by overvoltages we recommend to disconnect all cables from this device and your HiFi system during thunderstorms.

All mains power supply and aerial systems to which the unit is connected must meet all applicable safety regulations and must be installed by an approved electrical installer.

Approval and conformity with EC directives

In its original condition the unit meets all currently valid European regulations. It is approved for use as stipulated within the EC.

By attaching the CE symbol to the unit **T+A** declares its conformity the EC directives (See page 3) and the national laws based on those directives.

The original, unaltered factory serial number must be present on the outside of the unit and must be clearly legible! The serial number is a constituent part of our conformity declaration and therefore of the approval for operation of the device. The serial numbers on the unit and in the original **T+A** documentation supplied with it (in particular the inspection and guarantee certificates), must not be removed or modified, and must correspond.

Infringing any of these conditions invalidates **T+A** conformity and approval, and the unit may not be operated within the EC. Improper use of the equipment makes the user liable to penalty under current EC and national laws.

Any modifications or repairs to the unit, or any other intervention by a workshop or other third party not authorised by **T+A**, invalidates the approval and operational permit for the equipment.

Only genuine **T+A** accessories may be connected to the unit, or such auxiliary devices which are themselves approved and fulfil all currently valid legal requirements.

When used in conjunction with auxiliary devices or as part of a system this unit may only be used for the purposes stated in the section 'Approved usage'.

Disposing of this product



The only permissible method of disposing of this product is to take it to your local collection centre for electrical waste.

FCC Information to the user



(for use in the United States of America only)

Class B digital device - instructions:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different form that to which the receiver is connected.

Consult the dealer or an experienced radio/TV technician for help.

Network Configuration

General Information

The **CALA SR** can be operated in wired LAN networks (*Ethernet LAN* or *Powerline LAN*) or in wireless networks (*WLAN*).

If you wish to use your CALASR in your home network, you must first enter the necessary network settings on the CALASR. This includes entering the network parameters such as the IP address etc. both for wired and wireless operation. If you wish to use a wireless connection, a number of additional settings for the WLAN network also have to be entered.



In the following sections we assume that a working home network (cable network of WLAN network) with router and (DSL) Internet access is present.

If you are unclear about some aspect of installing, setting up and configuring your network, please address your queries to your network administrator or a network specialist.

Compatible hardware and UPnP servers

The marketplace offers a vast number of routers, NAS devices and USB hard discs made by a very wide range of manufacturers. **T+A** equipment is generally compatible with other makes of machine which bear the UPnP label.

Network settings menu

All network settings are entered in the Network Configuration menu. This menu will vary slightly in appearance depending on the type of your network, i.e. whether you have a wired (LAN) or wireless (WLAN) network.

If in the Network Configuration Menu the entry 'Network IF Mode' is set to 'auto', the CALA SR will check automatically if a LAN connection to a network is present. If a LAN connection is found, the machine will assume that this is to be used, and displays the network configuration menu for LAN networks. If no LAN network is connected, the CALA SR activates its WLAN module and displays the WLAN configuration menu when you call up the configuration menu. The menu for a WLAN network includes a number of additional menu points. The following sections explain how to use the menu, and the meaning of the individual menu points.

Opening the network settings menu

Open the System Configuration menu by pressing the **SYS** button on the remote control handset.

Use the _____ / ____ buttons to select the "Network" menu item, then confirm by pressing the _____ button.

Operating the menu, changing and storing IP addresses

	Use the / buttons in the menu to select the network parameter to be changed, and activate the entry with the button. You can now change the setting using the following buttons, depending
	on the type of setting:
	Numeric buttons to for entering IP addresses Alpha-numeric inputfor entering text
	When the setting process is complete, or when you have entered the complete address, press the ok button to confirm your action.
	Alpha-numeric entry
	At certain points, e.g. for entering server names or passwords, it is necessary to input series of characters (strings). At such points you can enter letters, numbers and special characters by repeatedly pressing the numeric buttons on the FM1000 remote control handset, as when writing SMS news. The assignment of letters to the buttons is printed below the buttons. Special characters can be accessed using the and buttons:
	0 + - * / ^ = { } () [] < > 1 . , ? ! : ; 1 \ " ' _ @ \$ % & # ~
	Use the blue button for toggling between numbers, capitals and lower-case letters. The bottom line of the screen shows which input mode is currently selected.
1	At certain points (e.g. DNS server name) it is possible to enter both an alpha-numeric string and an IP address. At these points an IP address should be entered like a string (with separating dots as special characters). In this case an automatic check for valid address ranges (0 255) is not carried out.
	Once you have correctly set all the parameters, select the menu item 'Store and exit?', then press the w button. This action causes the CALASR to accept the settings, and you should see the available network media sources (Internet radio LIPPE A) corner set; displayed in the main many.

Closing the menu

Interrupting the menu without storing the settings

At any time you can leave the network configuration menu without making any changes to the network settings: this is done by pressing the button, which takes you to the menu item 'Store and exit?'. If you wish to quit at this point without saving, use the / / V buttons to select the 'Discard and exit?' menu item, then confirm with the (oK) button.

The Configuration for a Wired Ethernet LAN or Power-Line LAN connection

Setting the Parameters for a Wired Network

- Connect the CALASR to an operational network or Power-Line modem using the LAN socket on the back panel.
- Open the System Configuration menu by pressing the system button on the remote control handset.
- Use the buttons to select the "Network" menu point, then confirm by pressing the button.
- You should now see the menu reproduced below, displaying the network parameters. In the title line the message 'LAN' should appear, indicating that the machine is connected to a wired LAN. If you see 'WLAN' at this point instead, please check your network connection, and ensure that the network is switched on and operational.
- You can now select the individual menu points and adjust them to match your network conditions. The illustration below shows the possible button inputs after each menu item.

Possible entries

Network settings menu		
MAC	00:0e:9b:cc:a4:35	none
Connection state	LAN	none
→ DHCP	Off	
IP	192.168.0.10	(0 9)
Subnet mask	255.255.255.0	(0 9)
Gateway	192.168.0.1	(0 9)
DNS	192.168.0.1	(0 9, A Z)
Store and exit?	apply	OK
Discard and exit?	apply	ОК

(0...9): Switching ON / OFF

Numeric input, separating dots are automatically generated; input limited to valid addresses

(0...9, A...Z): Alpha-numeric input and special characters.

IP - separating dots must be entered as special characters.

The parameters illustrated above are only typical values.

Addresses and settings may require different values for your network.

Menu Point	Description
MAC	The MAC address is a hardware address which uniquely identifies your machine. The address displayed is determined by the manufacturer, and cannot be altered.
Connection state	Shows the connection state: WLAN, LAN or not connected.
DHCP	ON If your network includes a DHCP server, please select the ON setting at this point. In this mode an IP address is automatically assigned to the CALA SR by the router. The screen shows only the MAC address and the message DHCP state ON. In this case the address input fields shown in the illustration do not appear in the menu.
	OFF If your network does not include a DHCP server, please select the OFF setting. In this mode you must configure the following network settings manually. Please ask your network administrator for the addresses to be entered for your network.
IP	IP address of the CALA SR
Subnet mask	Network mask
Gateway	IP address of the router
DNS	Name / IP of the name server (optional)
Store and exit?	Stores the network parameters, and restarts the ${\bf CALASR}$ with the new settings.
Discard and exit?	Closes the menu: data already entered is discarded.

The Configuration for a WLAN connection

Setting the parameters for a wireless network

- Now switch the CALASR on, and open the System Configuration menu by pressing the (sys) button on the remote control handset.
- Use the buttons to select the menu point "Network", then confirm your choice with the button.
- The following menu now opens:

	_ settings
00:0e:9b:cc:a4:35	none
apply	none
apply	ОК
Off	
192.168.0.10	(0 9)
255.255.255.0	(0 9)
192.168.0.1	(0 9)
192.168.0.1	(0 9, A Z)
apply	ОК
apply	ОК
	not connected apply apply Off 192.168.0.10 255.255.255.05 192.168.0.1 192.168.0.1 apply

Selecting and connecting a WLAN by hand

Searching for and Selecting the Network

- First select the menu point "Scan for WLAN", and activate it by pressing the ok button.
- A list of the WLANs found is displayed on the screen.
- Use the ▲ / ▼ buttons to select the WLAN to which you wish the CALASR to be connected, and confirm your choice with the ok button

Entering the Password (for encoded networks) If the network is encoded, the window shown below will appear once the WLAN is selected.

At this point please enter the network password and confirm your input by pressing $\overline{\text{ok}}$.

Select the "Store and exit?" point, and confirm your choice with OK.

SSID	XXXXXXXXX
Security	PSK
→ Passphrase	
Store and exit?	apply

Storing Network Settings and Restarting Finally select the "Store and exit?" menu point and press the button to accept the settings.

Connecting to WLAN via the WPS-function

WPS-function

The CALASR supports WPS for WLAN setup. WPS (Wi-Fi Protected Setup) an easy process for establishing a secure WLAN connection. WPS can be used to connect the CALASR with your router in a quick and convenient way. For that usage most modern routers have implemented the WPS function.

Connecting WLAN automatically via the WPS function

- First activate the WPS-function of the Router or Repeater to which you
 wish the CALASR to be connected. For details please refer the manual
 of the device in question.
- Start the WPS-Autoconnect function of the CALASR within 2 minutes.
- After the connection is established, the line "Status" shows the connected WLAN network.
- Finally select the "Store and exit?" menu point and press the ok button to accept the settings.

Selecting the WLAN manually and conneting via WPS If the WPS function connects the CALASR to the wrong WLAN, the preferred WLAN can be also selected manually and only the authentication can be done by the WPS function. The procedure is described in the following:

- First activate the WPS-function of the Router or Repeater to which you
 wish the CALASR to be connected. For details please refer the manual
 of the device in question.
- First select the menu point "Scan for WLANs", and activate it by pressing the (ok) button.
- A list of the WLANs found is displayed on the screen.

The window shown below will appear once the WLAN is selected:



- Select the "Security" menu point and press the
 ok button to activate it. Now select the setting "WPS" and confirm it with the
 ok button.
- Now select the "Store and exit?" menu point and press the ok button
- After the connection is established, the line "Status" shows the connected WLAN network.
- Finally select the "Store and exit?" menu point and press the ok button to accept the settings.

Trouble shooting

Many problems have a simple cause and a correspondingly simple solution. The following section describes a few difficulties you may encounter, and the measures you need to take to cure them. If you find it impossible to solve a problem with the help of these notes please disconnect the unit from the mains and ask your authorised **T+A** specialist dealer for advice.

Machine does not switch	Cause 1:
on	Mains lead not plugged in correctly.
OII	Remedy:
	Check connection, push connector in firmly.
Machine connet be	Course 4:
Machine cannot be	Cause 1:
controlled by IR remote	Incorrectly inserted batteries or flat batteries in the remote
control.	control handset.
	Remedy:
	Re-install batteries correctly or fit new ones.
	Cause 2:
	The remote control transmitter has no direct line-of-sight with
	the unit.
	Remedy:
	Make sure that the remote control transmitter has direct line-of-
	sight contact with the receiver - note that glass doors can
	interrupt the connection.
	Maximum range between transmitter and receiver: approx.
	8 metres.
	Be sure to position the receiver where it is not subjected to
	direct sunlight or very bright artificial light. Fluorescent tubes
	and energy-saving lamps are powerful sources of interference.
	g/gp
App cannot find the	Cause:
device in powered off	Energy saver is switched on.
state.	Remedy:
	Switch off the Energy saver function in the system
	configuration menu.
	g
The streaming client	Cause 1 (cable LAN):
cannot connect to a	Network cable not properly connected
network.	Remedy:
On the display the	Connect network cable, check connection to router
indication	Cause 2 (wireless LAN):
'Cannot connect to	WLAN antenna not connected or placed in a location with bad
network'	reception quality
is displayed.	Remedy:
is displayed.	Connect WLAN antenna properly and find a location with good
	reception quality.
	Set the transmission power output of your WLAN router to
	maximum.
	Try to establish a network connection first in a location close to
	the WLAN router. If this succeeded try to connect to WLAN
	from a more remote location. Experiment with antenna position
	and try to find a location with better reception quality.

Cause 3 (wireless LAN):

WLAN reception quality bad (low field strength). Possibly too much attenuated by walls/ceilings on the transmission path.

Remedy:

Optimize location of receiver and transmitter antennas.

Alternative:

If transmission problems persist a so called ,Power Line' network might be good alternative to establish a good and stable network connection.

The best, safest and most secure network however will always be a cable LAN network.

Cause 4:

Network parameters not properly configured.

Remedy:

Configure the network parameters correctly (see chapter 'Network configuration').

Cause 5 (operation without network connection):

For proper operation the **CALA SR** needs at least one properly connected network device. This can be a LAN or WLAN network or a USB storage device.

Remedy:

If the CALASR shall be operated without network (LAN / WLAN) please connect at least a USB stick.

Software update

Software update generally

Software updates keep your **CALA SR** up-to-date. They bring new optimisations like faster operation and new features which were not available at the time the device was produced.



It may occur that after a software update some of your user defined settings like network parameters or favourite stations are lost and have to be restored after the update.

Updating via the Internet

Updating the firmware via the CALA SR's Internet connection

- The basic requirement is a functioning network with router and access to a broadband Internet connection; the system must be operating.
- Switch the machine on.
- Call up the system configuration menu by pressing the sys button on the remote control handset.
- Use the buttons to select the "Device info" menuitem, and confirm your selection by pressing the button.
- The Select option "WEB" should now be active (highlighted).
- The firmware update can now be started by pressing (ox).
- The screen displays the current state of progress of the update.
- Once the update has been completed (duration around ten minutes) the device automatically switches itself off and restarts.
- When the machine has restarted, the update is complete.
- To ensure that the update was successful, access the "Device Info" menu point mentioned above, and check the new firmware status.

Notes on Energy Saving

General information

The CALASR satisfies the requirements of the latest directives concerning energy-saving measures (EuP directive). The modern design of the mains power supply makes an important contribution to this.

The internal micro-processor constantly ensures that sub-assemblies which are not currently required are automatically switched off. The micro-processor itself operates in stand-by mode at a relatively low clock speed, and only responds to the remote control receiver.

In stand-by mode the current drain of the **CALASR** is less than 0.5 Watt. If you intend not to use the device for a long period, it should be disconnected from the mains socket, i.e. the mains plug should be withdrawn from the wall socket.

Automatic power-down (Energy saver)


The device features an automatic power-down function. If the CALASR detects no operation or no music signal for a period longer than ninety minutes, it automatically switches to stand-by mode. Two minutes before the device enters the standby mode, a pop-up window appears on the screen. If the device should stay in operation please press the ok button while this message is displayed.



In countries outside the EU, in which the EuP directive has no validity, the automatic power-down feature can be disabled if necessary (see chapter entitled 'Basic settings of the CALASR).

Appendix A

Wiring diagram




Attention!

A properly set up home network with router must be installed and in operation to use the CALASR. For the use of internet radio a DSL access to the internet is needed.

For questions regarding setting up your network and internet connection please ask your system administrator or any network specialist.

- *1 Music server with UPnP-AV server software installed
- *2 Connection either via Cable-LAN or Wireless-LAN

Wiring diagram



Appendix B

Specification

Streaming Client		
Formats	MP3, WMA, AAC, AIFF, OGG-Vorbis, FLAC + WAV	
Data ratas	PCM 32192 kHz,16/32 Bit; MP3 up to 320	
Data rates	kBit; constant and variable data rate	
Services	Tidal, Deezer, qobuz (subscription required)	
Media server	UPnP AV, Media Player 10 (WMDRM10), DLNA compatible servers	
Interfaces	LAN: Fast Ethernet 10/100 Base-T, WLAN: 802.11 b/g/n with WPS	
Bluetooth		
	A2DP Bluetooth audio transfer protocol with AVRCP	
USB		
	1x USB 2.0 Mastermode	
Radios		
Internetradio	airable Internet Radio Service	
Internetiadio	(> 11000 Stations worldwide)	
FM, FM-HD	87,5 - 108 MHz; Sensitivity 1 μV;	
T W, T W T ID	S/N > 65 dBA	
DAB, DAB+	168 -240 MHz (Band III);	
	Sensitivity 2,0 μV, S/N > 96 dBA	
Features	RDS/RDBS, Station name (PS), Program type	
Amendifian Continu	(PTY), Radiotext (RT), Clock	
Amplifier Section	On ALIV FOOds / O 75V / OO bo consists a secretivity	
Inputs	2x AUX, 500mV2,75V / 20 kΩ variable sensitivity SP/DIF (16-24bit): 1x coax (192kHz), 2x TOS-Link (96kHz)	
RMS power output into 4 Ohms	2 x 55 Watt	
T.H.D.	<0.02 %	
Sound Management	DSP controlled sound characteristics	
Bass Management	Full range, 40 Hz, 60 Hz, 100 Hz, 150 Hz	
Dass Management	Pre-Amp, Subwoofer, Headphone	
Outputs	digital IEC 60958 (CDDA/LPCM)	
Power requirement	100 – 240 V, 50 – 60 Hz	
Power consumption	max. 150 W, Eco Standby <0,5 W, Comfort Standby 4 W (Display off), 7,5 W (Display on)	
Dimensions	10,5 x 37 x 24,5 cm	
Weight	6 kg	
Accessories	Remote control FM1000, WLAN antenna, VHF antenna, user manual	

We reserve the right to alter specifications.

Herford
Deutschland * Germany * Allemagne